## ottobock.

# Wingus

## Reliable and comfortable design



The Wingus is a sit-and-drive power wheelchair with a rear wheel drive that is equally suited for indoor and outdoor use. This compact, manoeuvrable entry-level model features an innovative, inherently resilient frame construction for high driving comfort. The Wingus combines reliable functionality with an appealing, minimalist design: Reliability made in Germany.

## **Highlights**

- High driving comfort thanks to innovative, inherently resilient frame construction
- Swing-away arm supports for straightforward side transfer
- Compact size allows the use in confined spaces
- Straightforward seat depth and lower leg length adjustment
- Seat belt for secure support
- Height adjustable legrest with foldable, angle-adjustable footplate
- Anti-tipper, installed
- Service-friendly with puncture-proof tyres
- Low product weight of 57 kg



 High driving comfort thanks to innovative, inherently resilient frame construction



Long-term tested batteries and motors



Parallel swing away control panel holder



Positioning belts for the feet


Splash guard for drive wheels



Electric lighting according to German Motor Vehicle Safety Standards (StVZO)



Adapter for head support mounting kit



Small storage bag underneath the seating area

## ottobock.

### Wingus

Art.-no. 490E163=00000

### **Options**

- Parallel swing away control panel holder
- Electric lighting according to German Motor Vehicle Safety Standards (StVZO) or footpath lighting
- Small storage bag underneath the seating area
- Splash guard for drive wheels
- Gel batteries
- Positioning belts for the feet
- Crutch holder
- Cupholder
- Pocket for mobile phone
- Can be combined with high-quality seat cushions and head supports from the Ottobock range of accessories
- Adapter for head support mounting kit

### Technical data

Application class	В
Seat width	400-460 mm
Seat depth	380/400/420/440/460/480 mm
Front seat height	500 mm
Overall length	
With foot plate flipped up With foot plate flipped down	893 mm 1,050 mm
Overall width	585 mm
Back support height	550 mm
Back support angle	0°/10°/20°
Lower leg length with 50 mm seat cushion (min./max.)	380 – 480 mm
Driving distance range	25 km
Max. obstacle negotiation capacity	50 mm
Nominal climbing ability	7° (12%)
Max. load	120 kg
Weight	57 kg



You may request the instructions for use with comprehensive information on the product as a PDF file at the email address oa@ottobock.com. The PDF file can also be displayed in a larger size.